

FISHING CUP

Fishing Cup

Fishing cup is applied mainly for fishing of shivers and fallen objects such as carbide tooth, drill bit and bearing that cannot be carried out of hole by convectional fluid circulation, etc. during drilling process. Fishing cup also possesses important functions to keep hole toe cleaning, increase bit service lift, reduce and prevent drill bit from unexpected damage. Such fishing cup tools are available with all sizes and super performance.



Fishing Cup

Technical Specifications of Fishing Cup

Fishing Cup Model	Suitable Hole Size (mm)	Thread Connection (in)	I.D. (mm)	O.D. (mm)
FC94	108~117.5	2-3/8 REG	19	94
FC 102	117.5~124	2-7/8 REG	32	102
FC 114	130~149	3-1/2 REG	38	114
FC 127	152.4~162	3-1/2 REG	38	127
FC 140	165~190.5	3-1/2 REG	38	140
FC 168	190.5~216	4-1/2 REG	57	168
FC 178	219~244.5	4-1/2 REG	57	178
FC 190	229~273	4-1/2 REG	57	190
FC 197	235~279.5	5-1/2 REG	70	197
FC 219	244~295	6-5/8 REG	89	219
FC 229	254~305	6-5/8 REG	70	229
FC 245	292~330	6-5/8 REG	89	245
FC 280	330~375	7-5/8 REG	89	280
FC 311	327~375	7-5/8 REG	89	311
FC 327	375~444.5	7-5/8 REG	102	327
FC 340	386~456	7-5/8 REG	102	340