

## Plug Valve

### Pressure Balanced Plug Valve

#### Main Technical Specifications:

<b>Design and Manufacture</b>	ASME B16.34, API 599, API 6D, API 6A
<b>Face to Face Dimension</b>	ASME B16.10, API 6A
<b>Flange Connection Dimension</b>	ASME B16.5, API 6A
<b>BW Connection Dimension</b>	ASME B16.25
<b>Threaded Ends Dimension</b>	ASME B1.20.1
<b>Socket Welded Ends Dimension</b>	ASME B16.11
<b>Pressure-Temperature Rating</b>	ASME B16.34
<b>Test and Inspection</b>	API 598, API 6D, API 6A
<b>Type of Operation</b>	Manual, Gear, Electric, Pneumatic, Hydraulic
<b>Nominal Diameter</b>	1/2" ~ 30"
<b>Nominal Pressure(Class)</b>	150Lb ~ 1500Lb
<b>Main Materials</b>	WCB, WCC, LCB, LCC, WC6, WC9, C5, C12, CF8, CF8M, CF3, CF3M, CF8C, CN7M, A105, LF2, F5, F9, F11, F22, F304, F304L, F316, F316L, F321



### Non-Lubricated Plug Valve

#### Main Technical Specifications

<b>Design and Manufacture</b>	ASME B16.34, API 599, API 6D, API 6A
<b>Face to Face Dimension</b>	ASME B16.10, API 6A
<b>Flange Connection Dimension</b>	ASME B16.5, API 6A
<b>BW Connection Dimension</b>	ASME B16.25
<b>Threaded Ends Dimension</b>	ASME B1.20.1
<b>Socket Welded Ends Dimension</b>	ASME B16.11
<b>Pressure-Temperature Rating</b>	ASME B16.34
<b>Test and Inspection</b>	API 598, API 6D, API 6A
<b>Type of Operation</b>	Manual, Gear, Electric, Pneumatic, Hydraulic
<b>Nominal Diameter</b>	1/2" ~ 20"
<b>Nominal Pressure(Class)</b>	150Lb ~ 600Lb
<b>Main Materials</b>	WCB, WCC, LCB, CF8, CF8M, CF3, CF3M, CF8C, CN7M, A105, F304, F304L, F316, F316L, F321

